<u>IN THE CLAIMS</u>

Please amend the claims as follows:

1. (original) Method of caching teletext page data in a memory unit (21) of a teletext receiver system, comprising

- receiving and storing in the memory unit (21) data representing a sequence of teletext pages embedded in a signal belonging to a first one of a plurality of channels; and

- subsequently receiving and storing in the memory unit (21) data representing a sequence of teletext pages embedded in a signal belonging to a further one of the plurality of channels, whilst keeping at least some of the previously stored teletext page data stored in the memory unit (21),

wherein for each received teletext page, it is determined whether the memory unit (21) has capacity available for storing the received teletext page data representing the received teletext page, and for each stored teletext page, information is stored associating the stored teletext page data representing the page with the channel to which the signal in which that teletext page data was embedded belongs, **characterised by,**

upon determining that the memory unit has insufficient capacity, substituting the teletext page data representing the received

teletext page for teletext page data associated with at least one
different channel.

2.   (original)   Method according to claim 1, comprising receiving a
user-initiated command requesting a desired teletext page, using
the stored information associating the teletext page data with a
channel to search for the teletext page data representing the
desired teletext page in the teletext page data associated with the
channel to which the signal belongs in which teletext page data
currently being received was embedded.

3.   (currently amended)   Method according to claim 1 or 2,
comprising storing information (15;24) reflecting at least one
usage statistic for at least each channel associated with teletext
page data stored in the memory unit (21) and selecting the teletext
page data for which the teletext page data representing the
received teletext page is substituted on the basis of the stored
information (15;24) reflecting the usage statistics.

4.   (original)   Method according to claim 3, comprising updating
the at least one usage statistic whenever teletext page data
associated with the channel is read from the memory unit (21).

5.	(currently amended)	Method according to claim 3 ~~or 4~~, wherein

the usage statistics comprise information (24) enabling

establishment of a ranking of all of the pages encoded by teletext

page data stored in the memory unit (21), based on a most recent

time of transfer in a pre-determined direction of the teletext page

data representing each page across an interface of the memory

unit (21).

6.	(currently amended)	Method according to ~~any one of~~

~~claims 3-5~~claim 3, wherein the teletext page data is received from

an arrangement of a channel selection circuit (3) and a teletext

data acquisition circuit (6), and the usage statistics for each

channel comprise information (15) representative of how often the

channel has been selected.

7.	(currently amended)	Method according to ~~claims 4, 5 and 6~~claim

4, wherein at least part of the teletext page data for which the

teletext page data representing the received teletext page is

substituted is the least recently transferred teletext page data

associated with the least often selected channel and selected on

the basis of the stored information (15;24) reflecting the usage

statistics.

8. (currently amended) Method according to ~~any one of~~
~~claims 3-6~~claim 3, wherein the teletext page data is received from
an arrangement of a channel selection circuit (3) and a teletext
data acquisition circuit (6), and the usage statistics for each
channel comprise information enabling establishment of a ranking of
channels according to a most recent time of selection of each
channel.

9. (original) Method according to claim 8, wherein at least part
of the teletext page data for which the teletext page data
representing the received teletext page is substituted is selected
from among teletext page data stored in the memory unit (21) and
associated with a channel other than a most recently selected of
the channels associated with teletext page data stored in the
memory unit (21), preferably the least recently selected.

10. (currently amended) Teletext receiver system, comprising a
controller (7) and a memory unit (21) arranged to receive data
representing teletext pages from an arrangement of a channel
selection circuit (3) and a teletext data acquisition circuit (6),
which teletext receiver system is arranged to carry out a method
according to ~~any one of claims 1-9~~claim 1.

11. (currently amended) Television set, comprising a controller (7) and a memory unit (21) arranged to receive data representing teletext pages from an arrangement of a channel selection circuit (3) and a teletext data acquisition circuit (6), which teletext receiver system is arranged to carry out a method according to ~~any one of claims 1-9~~claim 1.

12. (currently amended) Computer program, capable, when run on a computer arranged to receive data representing teletext pages from an arrangement of a channel selection circuit (3) and a teletext data acquisition circuit (6), of enabling the computer to carry out a method according to ~~any one of claims 1-9~~claim 1.